

BENEFITS

▲ Rich visual Experience | The C63G/C63GP is an entry-level IP phone, and the C63G/C63GP features a 2.4" high-resolution color TFT display with backlight, which takes visual effects to a new level. The freely programmable multi-color function keys provide users with a high degree of usability. Each function key can be configured for various one-touch phone functions such as speed dial, busy lamp field, etc.

C63G/C63GP at Parking Office

- ▲ Good Compatibility | Based on RFC3261, the C63G/C63GP has been tested to ensure good compatibility with leading IP telephony system and equipments. The C63G/C63GP not only supports Dinstar UC/IPPBX products, also supports many third-party IPPBXs such as 3CX, Asterisk, NEC, Grandstream and so on.
- ▲ High Quality Audio | The full duplex speaker and microphone system and the Digital Signal Processor (DSP) ensure that the C63G/C63GP delivers high audio quality. Whether you use the hands-free speaker-phone or the handset, you will always have good experience and crystal-clear call quality. HD Voice, Up to 6 SIP Accounts, 2.8" 320 x 240 pixel TFT LCD with Backlight, Dual-port Gigabit Ethernet, Power over Ethernet, Support EHS wireless headset(Plantronics, Jabra, Sennheiser), Stand with 2 adjustable angles, Full Compatible with 3CX,Asterisk, Broadsoft, Freeswitch Platform etc.





CALL FEATURES

PHYSICAL FEATURES

Model	Screen	Network	PoE Support	Power Adapter
C63G	2.8" Color Screen	10/100/ 1000Mbps	х	✓
C63GP	2.8" Color Screen	10/100/ 1000Mbps	1	Х

SPECIFICATIONS

	* Blind/attended transfer * Call hold, Call mute, DND mode * Speed Dialing, Hotline *Redial, Call Return * Auto-redial, Auto-answer * Dial Plan * 5-way conference * Peer Dialing
PHONE FEATURES	* Adjustable Voice Volume * Selectable Ring Tones * XML Browser * Action URL/URI * Keyboard lock * Phonebook: 1000 Groups * Blacklist: 100 Groups * Call Log: 100 Logs * Support 5 Remote Phonebook URLs * LDAP * Support Multiple Languages * Support EHS wireless headset(Plantronics, Jabra, Sennheiser)
IP-PBX FEATURES	* SMS, Voicemail, MWI * Music On-hold, Intercom, Multicast * Call Pickup, Call Pickup in Group * Anonymous Call * Anonymous Call Rejection
MANAGEMENT	* Auto provisioning: FTP/TFTP/HTTP/HTTPS/PnP * Configuration via HTTP/HTTPS web * SNMP, TR069 * Network capture * NTP/Daylight saving time *Firmware upgrade via web * Syslog * Configuration backup/restore *Equipment Management System (NMS)
AUDIO	* HD Voice * Wideband Codec: G.722, OPUS-WB * Narrowband Codec: PCMA, PCMU, G.729, G723, G726, AMR, OPUS, iLBC * Echo Cancellation/Dynamic Jitter * Voice Activity Detection (VAD) * Comfort Noise Generation (CNG) * Full-duplex Speaker
PROTOCOLS & STANDARDS	* SIP v1 (RFC2543), SIP v2 (RFC3261) * SIP over TLS, SRTP * TCP/IP/UDP * RTP/RTCP, RFC2198, RFC1889 * HTTP/HTTPS/FTP/TFTP * ARP/RARP/ICMP/NTP/DHCP *DNS SRV/ A Query/NATPR Query * STUN, Session Timer (RFC4028) *DTMF: In-Band, RFC2833, SIP INFO * LLDP * 802.1X, OpenVPN

* Color 2.8" High resolution screen (320x240) * Dual-angle foot stand: 40° and 55°

* Environmental conditions: Operation temperature: 0~40°C, Humidity: 10% to 95% (non-condensing)

* Dimensions(approx.): - 201x203x42.5mm(WxLxD)w/o foot stand * Weight(approx.): device 550g, foot stand 50g * Input voltage: 5Vdc

* Headset: 4P4C, RJ9 * Extended interface: 6P6C, RJ12

* Power supply: PoE or 5Vdc power adapter * PoE IEEE802.3af * Handset: 4P4C, RJ9

* 2xRJ45 10/100/1000M Ethernet Ports

* Wall Mountable

* 6 SIP Accounts * Call Waiting * Call Forward